



| REV. | REVISION RECORD | DATE | REV. | REVISION RECORD | DATE |
|------|-----------------|------|------|-----------------|------|
| A    |                 |      | C    |                 |      |
| B    |                 |      | D    |                 |      |

|                                                 |                 |              |                                                                                                                                                                                         |       |       |        |               |       |
|-------------------------------------------------|-----------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|--------|---------------|-------|
| NAME                                            | ERL-28-11 (12P) | MATERIAL     | PHENOLIC                                                                                                                                                                                | SCALE | 1.5/1 | ANGLE: | $\pm 1^\circ$ |       |
| DRAWING NO.                                     | HY 2827         | PIN MATERIAL | CP WIRE                                                                                                                                                                                 | UNIT  | m/m   | REV.:  | A             |       |
| TOLERANCE OF PIN PITCH                          | $\pm 0.20$      |              | 信詠塑膠工業股份有限公司<br>HSIN YUNG PLASTIC INDUSTRIAL CO.,LTD.<br>TEL:886-2-29953711 FAX:886-2-29990010<br>信詠塑膠電子廠<br>HSIN YUNG PLASTIC ELECTRONICS FACTORY<br>TEL:0769-6632011 FAX:0769-6635843 |       |       |        |               |       |
| PIN TENSION LOAD                                | 1.2kg MIN       | UL REC.:     |                                                                                                                                                                                         |       |       |        |               | 94V-0 |
| TOLERANCES: 0<L≤4:±0.1 4<L≤16:±0.2 16<L≤63:±0.3 |                 |              |                                                                                                                                                                                         |       |       |        |               |       |