



| | |
|----------|--------|
| A | 代表重要尺寸 |
| Ⓐ | 代表次要尺寸 |

檢驗條件: 此產品是符合ROHS要求的。

| REV. | REVISION RECORD | DATE | REV. | REVISION RECORD | DATE |
|------|-----------------|-----------|------|-----------------|------|
| A | | | C | | |
| B | 改善過線槽 | 2008.7.11 | D | | |

| | | | | | | | |
|---|-------------------------------------|--------------|--|-------|-------|--------|-----|
| NAME | PQ3220-2(12PIN) | MATERIAL | PM9820 | SCALE | 1.2/1 | ANGLE: | ±1° |
| DRAWING NO. | HY3207 | PIN MATERIAL | CP WIRE | UNIT | m/m | REV.: | B |
| UL REC.:94V-0 | PIN TENION LOAD: 1.0kg MIN | |  信詠塑膠工業股份有限公司 HSIN YUNG PLASTIC INDUSTRIAL CO., LTD. TEL:886-2-29953711 FAX:886-2-29990010 信詠塑膠電子廠 HSIN YUNG PLASTIC ELECTRONICS FACTORY TEL:0769-86632011 FAX:0769-86635843 | | | | |
| TOLERANCES: | 0<L≤4:±0.1 4<L≤16:±0.2 16<L≤63:±0.3 | | | | | | |
|  | PIN PITCH:±0.2 WALL THICKNESS:±0.15 | | | | | | |